

18W2000

High Output LF Ferrite Transducer


99 dB SPL 1W / 1m average sensitivity
 100 mm (4 in) Interleaved Sandwich ISV copper voice coil
 1200 W AES power handling
 Double Silicon Spider (DSS) for improved excursion control and linearity
 Improved heat dissipation via unique basket design and multi-cell air diffractor
 Weather protected cone and plates for outdoor usage
 Suitable for high SPL subwoofer designs



GENERAL SPECIFICATIONS

Nominal Diameter	460 mm (18 in)
Rated Impedance	8 Ohm
AES Power (1)	1200 W
Program Power (2)	2400 W
Peak Power	7000 W
Sensitivity (3)	99 dB
Frequency Range (4)	37 - 3000 Hz
Power Compression @-10dB	0,5 dB
Power Compression @-3dB	1,5 dB
Power Compression @Full Power	2,2 dB
Max Recomm. Frequency	500 Hz
Recomm. Enclosure Volume	120 - 300 lt. (4,24 - 10,60 cuft)
Minimum Impedance	7,3 Ohm at 25°C
Max Peak To Peak Excursion	36 mm (1,42 in)

FREQUENCY RESPONSE CURVE




FREQUENCY RESPONSE CURVE OF 18W2000 MADE ON 180 LIT. ENCLOSURE TUNED 35HZ IN FREE FIELD (4PI) ENVIRONMENT. ENCLOSURE CLOSES THE REAR OF THE DRIVER. THE THIN LINE REPRESENTS 45 DEG. OFF AXIS FREQUENCY RESPONSE

THIELE SMALL PARAMETERS (5)

Fs	37 Hz
Re	5,8 Ohm
Sd	0,1134 sq.mt. (175,7 sq.in.)
Qms	7,29
Qes	0,26
Qts	0,25
Vas	230 lt. (8,12 cuft)
Mms	143 gr. (0,32 lb)
BL	27,1 Tm
Linear Mathematical Xmax (6)	± 7 mm (±0,28 in)
le (1kHz)	1,90 mH
Ref. Efficiency 1W@1m (half space)	98,6 dB

FREE AIR IMPEDANCE MAGNITUDE CURVE



FREE AIR IMPEDANCE MAGNITUDE CURVE

MOUNTING INFORMATION

Overall diameter	462 mm (18,18 in)
N. of mounting holes and bolt	8
Mounting holes diameter	8,5 mm (0,33 in)
Bolt circle diameter	438-440 mm (17,24-17,32 in)
Front mount baffle cutout Ø	416 mm (16,38 in)
Rear mount baffle cutout Ø	412 mm (16,22 in)
Total depth	205,9 mm (8,1 in)
Flange and gasket thickness	19 mm (0,75 in)
Net weight	11,5 kg (26,35 lb)
Shipping weight	13 kg (28,66 lb)
CardBoard Packaging dimensions	482 x 482 x 257 mm (19 x 19 x 10,1 in)

NOTES

- (1) AES power is determined according to AES2-1984 (r2003) standard
- (2) Program power rating is measured in 180 lit enclosure tuned 35Hz using a 40 - 400Hz band limited pink noise test signal with 50% duty cycle, applied for 2 hours.
- (3) Sensitivity represents the averaged value of acoustic output as measured on the forward central axis of cone, at distance 1m from the baffle panel, when connected to 2,83V sine wave test signal swept between 100Hz and 500Hz with the test specimen mounted in the same enclosure as given for (1) above.
- (4) Frequency range is given as the band of frequencies delineated by the lower and upper limits where the output level drops by 10 dB below the rated sensitivity in half space environment.
- (5) Thiele - Small parameters are measured after the test specimen has been conditioned by AES power and represent the expected long term parameters after a short period of use.
- (6) Linear Math. Xmax is calculated as $(HvcHg)/2 + Hg/4$ where Hvc is the coil depth and Hg is the gap depth.